D-Link Switch 5 Porte Gigabit Case Metallico

D-LINK · Networking · Nuovo



PREZZO

40,90 € IVA inclusa

DESCRIZIONE

D-Link DGS-105. Trasmissione dati: 1 Gbit/s, 10/100/1000Mbps, 2000 Mbit/s, 10 Gbit/s. Networking: 2000 ENTRATE, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x. Caratteristiche di gestione: No gestito. Connettività: 1000BASE-T, 100BASE-TX, 10BASE-T. Memoria: 0.128 MB. Peso e dimensioni: 100 x 98 x 28 mm, 286 g. Gestione energetica: 3.10 W, 1 A, 5 V. Durata: 1688338 h. Certificati di sicurezza: FCC Class B, ICES-003 Class B, CE Class B, C-Tick Class B, VCCI Class B, cUL, CB, RoHS. Condizioni ambientali: 10 - 90 %, 0 - 50 °C, 10 - 70 °C, 5 - 90 %. Illuminazione/Allarmi: Link, Power, Si. Colori: Nero. Material: Metallo

Standards

- IEEE 802.3 10BASE-T Ethernet

- IEEE 802.3u 100BASE-TX Fast Ethernet

- IEEE 802.3ab 1000BASE-T Gigabit Ethernet

- ANSI/IEEE 802.3 NWay auto-negotiation

- IEEE 802.3x flow control

- IEEE 802.3az Energy Efficient Ethernet (EEE)

Layer2 Features

- MAC address table: 2K

- Auto MDI/MDIX crossover for all ports

- Store-and-forward switching scheme

- Full/half-duplex for Ethernet/Fast Ethernet speeds

- Full-duplex only for Gigabit Ethernet speed

- Jumbo Frames: 9000 Bytes

Switching fabric

- 10 Gbps

Data Transfer Rates

- Ethernet: 10 Mbps (half duplex), 20 Mbps (full duplex)

- Fast Ethernet: 100 Mbps (half duplex), 200 Mbps (full duplex)

- Gigabit Ethernet: 2000 Mbps (full duplex)

Packet Filtering/Forwarding Rates

- Ethernet: 14,880 pps per port

- Fast Ethernet: 148,800 pps per port

- Gigabit Ethernet: 1,488,000 pps per port

RAM Buffer

- 128 KB

LED Indicators

- Per port: Link/Activity/Speed

- Per device: Power

Quality of Service (QoS)

- Supports 802.1p QoS

- 4 Queues, Strict Mode

Green features

- Energy Efficient Ethernet (EEE) standard

- D-Link Green: power saving by cable length detection

- RoHS compliant

Power

- External 5 V/1 A Level “V” Power Adapter

Power Consumption (DC input)

- Standby: 0.5 W.

- Maximum: 2.01 W.

MTBF

- 1,688,338 hours

Temperature

- Operating: 0 to 50 ˚C

- Storage: -10 to 70 ˚C

Humidity

- Operating: 10% to 90% RH non-condensing

- Storage: 5% to 90% RH non-condensing

Dimensions (W x D x H)

- 100 x 98 x 28 mm

Certifications

- FCC Class B

- ICES-003 Class B

- CE Class B

- C-Tick Class B

- VCCI Class B

- cUL

- CB

SPECIFICHE TECNICHE

Caratteristica	Dettaglio
SKU	MPI-174C3AA36B
EAN	0790069368226
Condizione	Nuovo

Scheda tecnica generata il 25 novembre 2026. Prezzi e disponibilità possono subire variazioni; fanno fede le condizioni pubblicate su mpinformaticasrl.it al momento dell'ordine.